

SPECIFICATION

ENCODER-EQUIPPED SEALING DEVICE

BACKGROUND

Field of the Invention

[0001] The present invention relates to an improvement to and/or in ~~the~~an encoder-equipped sealing device or sealing device that has a magnet-based encoder incorporated therein. More particularly, the present invention relates to such encoder-equipped sealing device that provides ~~the~~ capabilities for preventing ~~the~~ physical cohesion by ~~the~~ magnetic attraction from occurring between two or more units of ~~the~~ encoder-based sealing devices that are adjacent to each other, when ~~these~~these units are placed one over another so that ~~these~~units they are oriented in one particular direction.

Description of the Prior Art

[0002] ~~The~~An encoder (pulse coder) that is incorporated in the encoder-equipped sealing device that has been described above takes the form of a pulse generator ring that may be mounted on an automotive vehicle in order to flexibly control ~~the~~a device that ensures that the vehicle can be running with safety and stability, such as ~~the~~an anti-lock braking system (ABS), traction control system (TCS) and stability control system (SCS). This encoder may be mounted on ~~the~~a hub flange in ~~the~~a suspension system together with a sensor, and is used to detect ~~the~~a number of revolutions for each of the vehicle wheels. The encoder is mounted on each of ~~the~~ four wheels, such as front, rear, right and left wheels, together with the sensor, and may be used to detect any difference in ~~the~~a number of revolutions between each of the wheels. In response to such difference, the encoder may turn ~~the~~a drive system or brake system on and off, thereby controlling ~~the~~ behavior of the vehicle to ensure that the vehicle can be running with stability and safety in case some emergency ~~situations~~situation should occur.

[0003] Lubrication ~~oils~~oil may leak from ~~the~~ bearing units on the automotive vehicle on which the safety running devices are installed as described above, and seals are required to avoid such leaks. Most of the sealing devices include integrated sealing and ~~rotations~~rotation detecting capabilities, and may be mounted ~~on the~~in a gap or space that is available on the bearing units to meet such needs.

[0004] Typically, ~~the a~~ sealing device that has been proposed for those recent years provides ~~the rotations~~ a rotation detecting function as well as encoder function, and has been used widely for ~~the~~ practical purposes.

[0005] The typical encoder-equipped sealing device that has been proposed and practically used will be described below by referring to Fig. 8.

[0006] Two units 41, 42 of the encoder-equipped sealing device are shown in Fig. 8, in which each of the units includes two seal elements 3, 2 combined together.

[0007] Specifically, the seal elements element 3 includes a metal core 31 having a substantially L-shaped cross section, wherein the metal core 31 has a cylindrical portion 31a and a flange portion 31b extending from one end of the cylindrical portion 31a in ~~the a~~ direction perpendicular to ~~the a~~ direction in which the cylindrical portion 31a extends. The seal element 3 further includes an elastic seal portion 6 on the flange portion 31b that is arranged in ~~the a~~ space defined by the cylindrical portion 31a and flange portion 31b.

[0008] Similarly to the seal element 3, the seal element 2 ~~also~~ includes a metal core 21 having a substantially L-shaped cross section, wherein the metal core 21 has a cylindrical portion 21a and a flange portion 21b extending from one end of the cylindrical portion 21a in ~~the a~~ direction perpendicular to ~~the a~~ direction in which the cylindrical portion 21a extends. The seal element 2 further includes a magnet-based encoder 1 that is arranged on the flange portion 21b.

[0009] It may be seen from Fig. 8 that the seal element 3 and seal element 2 are combined such that the space defined by the cylindrical portion 31a and flange portion 31b of the seal element 3 and the space defined by the cylindrical portion 21a and flange portion 21b of the seal element 2 face opposite each other.

[0010] The encoder-equipped sealing device that includes ~~the~~ combined seal elements 3 and 2 may be mounted on any area that ~~need~~ needs to be sealed, such as ~~the an~~ appropriate area in ~~the a~~ bearing unit on ~~the an~~ automotive vehicle, and a sensor 11 shown by dot-dash lines in Fig. 2 may be mounted adjacently to the encoder 1 so that it can face opposite the encoder 1. It may be seen from Fig. 8 that in ~~the~~ unit 41, for example, the seal element 2 including the encoder 1 may be mounted on ~~the a~~ rotational element, such as ~~the an~~ inner or outer race of ~~the a~~ bearing unit, wherein ~~the~~ pulses that are magnetically generated by the encoder 1 may be detected by the sensor 11.

[0011] All of the encoder-equipped sealing devices that have been described above may be maintained in storage before they are actually used, such as being mounted on ~~the~~ areas of the bearing units on ~~the~~ an automotive vehicle that need to be sealed, and each of the devices has the seal elements 2, 3 completely assembled together. In storage, ~~the~~ these individual devices are maintained like a stack in which the devices are placed one over another such that they can be oriented in one particular direction, for ~~the~~ convenience of ~~the~~ easy ~~handling~~ handling by the appropriate handling tools. It may be seen from Fig. 8 that two units 41, 42 of the encoder-equipped sealing device, for example, are placed one over the other in ~~the~~ a horizontal direction such that each encoder 1 is located on the right side, and is oriented in one particular direction.

[0012] ~~The plural~~ Plural units of the encoder-equipped sealing device that are placed one over the other such that they are oriented in one particular direction, as shown in Fig. 8, are loaded in a magazine, and they are transported or ~~stored~~ with stored while being placed one over another such that they are oriented in one particular direction in the magazine. When they are actually used, they are removed from ~~the~~ respective magazines, and are mounted on ~~the~~ areas of ~~the~~ a bearing unit that need to be sealed.

[0013] In the plural units of the encoder-equipped sealing device that are placed one over the other so that they are oriented in one particular direction as shown in Fig. 8, the encoder 1 in ~~the~~ unit 41, for example, produces a strong magnetic force that attracts ~~the~~ metal core 31 on the seal element 3 in the other unit 42 magnetically. This may cause ~~the~~ cohesion by ~~the~~ magnetic attraction to occur between the seal element 2 in ~~the~~ unit 41 and the seal element 3 in the other unit 42.

[0014] When such cohesion occurs, the two units may attract each other magnetically within the magazine, from which it is difficult to remove the units by using any appropriate fitting device that mounts the units on ~~the~~ an area that needs to be sealed, such as ~~the~~ an appropriate area in ~~the~~ a bearing unit. This may cause the fitting device to become non-operational or may affect ~~the~~ a working efficiency of the fitting device remarkably.

[0015] In another encoder-equipped sealing device that is proposed to address the problem described above, which is disclosed in Japanese patent application as published under No. 2001-141069, ~~the~~ a seal portion is extended to provide a projection thereon. ~~The~~ An object ~~to provide~~ of providing this projection is to keep the two units of the encoder-equipped sealing device that are located ~~adjacently~~ to adjacent each other spaced away from each other. As this

projection is formed as part of ~~the~~an elastic seal portion, the projection thus obtained is not sufficient to prevent ~~the~~ cohesion by ~~the~~ magnetic attraction that occurs between the two units.

## SUMMARY OF THE INVENTION

[0016] In order to eliminate ~~the~~ serious disadvantages and problems associated with the prior art encoder-equipped sealing devices described above, it is an object of the present invention to provide an encoder-equipped sealing device that has a simple construction and prevents ~~the~~ cohesion by ~~the~~ magnetic attraction that might otherwise occur between ~~the~~ two units of the encoder-equipped sealing device that are located ~~adjacently to~~ adjacent each other. That is to say, the object of the present invention is to provide encoder-equipped sealing devices by which ~~the~~an encoder-equipped sealing device can be removed from ~~the~~a magazine without being caught by ~~each other~~ another encoder-equipped sealing device, and then may be mounted securely on ~~the~~an area that needs to be sealed, such as ~~the~~an appropriate area in ~~the~~a bearing unit, even if ~~the~~ plural units of the encoder-equipped sealing device are placed one over ~~the other~~ another such that they are oriented in one particular direction, as shown in Fig. 8, and loaded in a magazine.

[0017] The problems mentioned above may be solved by providing ~~the~~an encoder-equipped sealing device in accordance with the present invention that is constructed as described below.

[0018] The encoder-equipped sealing device that is proposed by the present invention comprises two seal elements 3, 2 combined together, wherein each of the elements 3, 2 includes a metal core 31, 32 having a substantially L-shaped cross section, with each of the metal cores 31, 32 having a cylindrical portion 31a, 21a and a flange portion 31b, 21b provided on one end of the cylindrical portion 31a, 21a and extending in ~~the~~a direction perpendicular to ~~the~~a direction in which the cylindrical portion 31a, 21a extends.

[0019] One seal element 3 and the other seal element 2 are combined together such that ~~the~~a space defined by the cylindrical portion 31a and flange portion 31b of the one seal element 3, and the space defined by the cylindrical portion 21a and flange portion 21b of the other seal element 2, face opposite each other.

[0020] The one seal element 3 further includes an elastic seal portion 6 on the flange portion 31b that is arranged in the space defined by its cylindrical portion 31a and flange portion

31b, and the other seal element 2 further includes a magnet-based encoder 1 on the flange portion 21b.

[0021] ~~In~~ ~~For the before-described~~ above-described encoder-equipped sealing device, the present invention proposes the following seven embodiments.

[0022] In an encoder-equipped sealing device according to a first embodiment of the present invention, that is shown in Fig. 1, one seal element 3 further includes a projecting portion 4a on ~~the~~ an end of ~~the~~ cylindrical portion 31a on ~~the~~ a side on which ~~the~~ flange portion 31b is located, wherein the projecting portion 4a extends beyond ~~the~~ a side of the flange portion 31b opposite ~~the~~ a side on which ~~the~~ seal portion 6 is located and in ~~the~~ a direction in which the cylindrical portion 31a extends.

[0023] In an encoder-equipped sealing device according to a second embodiment of the present invention, that is shown in Fig 2 and is a variation of the encoder-equipped sealing device according to the first embodiment, one seal element 3 includes an end 4b at ~~the~~ an end of ~~the~~ cylindrical portion 31a on which ~~the~~ flange portion 31b is located, and wherein the ~~said~~ end 4b ~~forming~~ forms a projecting portion ~~is formed by folding~~ the a base end of the flange portion 31b and the end of the cylindrical portion 31a ~~thereby overlapping so as to overlap~~ each other in ~~the~~ a direction in which the cylindrical portion 31a extends.

[0024] In an encoder-equipped sealing device according to a third embodiment of the present invention, that is shown in Fig. 3, one seal element 3 further includes a projecting portion 4c extending beyond ~~the~~ a side of ~~the~~ flange portion 31b opposite ~~the~~ a side on which ~~the~~ seal portion 6 is located and extending in ~~the~~ a direction in which ~~the~~ cylindrical portion 31a extends.

[0025] In an encoder-equipped sealing device according to a fourth embodiment of the present invention, that is shown in Fig. 5, ~~the~~ an end portion 4d of ~~the~~ cylindrical portion 31a of ~~the~~ one seal element 3 extending toward the other seal element 2 ~~is extending~~ extends in ~~the~~ a direction in which ~~the~~ cylindrical portion 31a extends and beyond ~~the~~ a side of the other seal element 2 opposite ~~the~~ a side on which the other seal element 2 faces opposite the one seal element 3.

[0026] In an encoder-equipped sealing device according to a fifth embodiment of the present invention, that is shown in Fig. 4, one seal element 3 further includes a recess 4f that is formed on ~~the~~ a side of ~~the~~ flange portion 31b opposite ~~the~~ a side on which ~~the~~ seal portion 6 is located, wherein the ~~said~~ recess 4f extends toward the side on which the seal portion 6 is located.

[0027] In an encoder-equipped sealing device according to a sixth embodiment of the present invention, that is shown in Fig. 6, ~~the~~ encoder 1 is arranged on ~~the~~ a side of ~~the~~ flange portion 21b of ~~the~~ other seal element 2 opposite ~~the~~ a side on which the flange portion 21b faces opposite ~~the~~ one seal element 3, and wherein the flange portion 21b includes a projecting portion 4e that extends beyond ~~the~~ a surface of the encoder 1 and in ~~the~~ a direction in which the cylindrical portion 21a extends.

[0028] In an encoder-equipped sealing device according to a seventh embodiment of the present invention, that is shown in Fig. 7, one seal element 3 ~~further~~ includes an elastic lateral side portion 5 formed on ~~the~~ a side of ~~the~~ flange portion 31b opposite ~~the~~ a side on which ~~the~~ seal portion 6 is located, and wherein the elastic lateral side portion 5 has undulations 4g formed thereon

[0029] In any of ~~the before described~~ these above-described embodiments, ~~the~~ seal portion 6 may be formed from any elastic ~~materials~~ material such as synthetic rubber, synthetic resin and the like, and ~~the~~ annular metal core 21, 31 may be formed from iron or stainless steel ~~materials~~. The encoder 1 is a multi-pole magnet that may be formed like an annular magnet from a mixture composed of any elastic material, such as synthetic rubber, synthetic resin or like, and any ferromagnetic material such as ferrite, rare earth or the like, in powdery forms. The annular magnet has N polarities and S polarities magnetized alternately around ~~the~~ its circumference. The ~~before described~~ above-described seal portion, annular metal core, and encoder are known and used in the conventional encoder-equipped sealing device comprised by ~~incorporating~~ incorporating an encoder and sealing elements combined together, and mounted on ~~the~~ a bearing unit ~~on the~~ in an automotive vehicle's wheel.

[0030] The encoder-equipped sealing devices that have been described in connection with the ~~before described~~ above-described embodiments are used together with a sensor that may be disposed ~~adjacently to~~ adjacent and opposite ~~the~~ encoder 1 so that it can detect ~~the~~ pulses that are generated magnetically by the encoder 1. ~~The~~ This magnet-based encoder 1 that is located on ~~the~~ a seal element mounted on ~~the~~ a rotational element on ~~the~~ an automotive vehicle ~~are~~ is rotated as the rotational element rotates, and the pulses from the encoder 1 rotating as the before described are detected by the sensor. Thereby, ~~the~~ a number of revolutions are detected by the sensor. It may be understood from the foregoing description that the encoder-equipped sealing device of the present invention has the encoder 1 incorporated therein.

[0031] In any of the first, second, third, fourth and sixth embodiments of the present invention, when ~~the plural units of the encoder-equipped sealing device of the present invention are placed one over the other adjacently to another adjacent~~ each other so that they are oriented in one particular direction, for example, when two units 51, 52 of the encoder-equipped sealing device are placed one over ~~the other adjacently to another adjacent~~ each other so that they are oriented in one particular direction as shown in Fig. 1, ~~the these~~ two adjacent units 51 and 52 can be kept spaced away from each other by the cylindrical portion or flange portion of the metal core. This can ~~keep the~~ maintain a gap between the two adjacent units 51 and 52 constant, and ~~the physical cohesion by the magnetic attraction that would occur between the two units 51 and 52~~ can thus be prevented effectively.

[0032] In the fifth embodiment, when ~~the plural units of the encoder-equipped sealing device of the present invention are placed one over the other adjacently to another adjacent~~ each other so that they are oriented in one particular direction, for example, when two units 51, 52 of the encoder-equipped sealing device are placed one over the other ~~adjacently to adjacent~~ each other so that they are oriented in one particular direction as shown in Fig. 1, ~~the an~~ area of contact between the encoder and the flange portion of the metal core can be kept as small as possible, and ~~the physical cohesion by the magnetic attraction that would occur between the two units~~ can thus be prevented effectively.

[0033] In the seventh embodiment, when ~~the plural units of the encoder-equipped sealing device of the present invention are placed one over the other adjacently to another adjacent~~ each other so that they are oriented in one particular direction, for example, when two units 51, 52 of the encoder-equipped sealing device are placed one over the other ~~adjacently to adjacent~~ each other so that they are oriented in one particular direction as shown in Fig. 1, ~~the a~~ gap between ~~the these~~ two adjacent units can be kept constant by the elastic lateral side portion 5 having the undulations 4g formed thereon, and ~~the physical cohesion by the magnetic attraction that would occur between the two units~~ can thus be prevented effectively.

[0034] It may be understood from the above description that when plural units of the encoder-equipped sealing device of the present invention are placed one over ~~the other another~~ so that they are oriented in one particular direction as shown in Fig. 1, ~~the cohesion by the magnetic attraction that might otherwise occur between the adjacent units~~ can be prevented effectively. ~~So that~~ Accordingly, even if the plural units of the encoder-equipped sealing device

are loaded in ~~the~~a magazine, with the units being placed one over ~~the other~~another so that they are oriented in one particular direction, ~~the~~each encoder-equipped sealing device can be removed from the magazine without being caught by ~~each other~~an adjacent encoder-equipped sealing device, and can then be mounted securely onto ~~the~~an area that needs to be sealed, such as ~~the~~an appropriate area in ~~the~~a bearing unit.

[0035] That is to say, even if ~~the~~ plural units of the encoder-equipped sealing device are placed one over ~~the other~~another so that they are oriented in one particular direction, ~~the~~each encoder-equipped sealing device can be ~~slided~~slid relative to ~~the other~~an adjacent encoder-equipped sealing device without causing any problems. Also, either of ~~the~~these two units that are located adjacently can be moved away from the other without causing any problems, so that each of the encoder-equipped sealing devices can be handled after ~~detaching each other~~being detached. Thus, the encoder-equipped sealing device of the present invention can be slid smoothly out of ~~the~~a magazine equipped in ~~the~~a fitting tool, without causing any problems such as being caught or stuck. Thus, the encoder-equipped sealing device can be mounted on ~~the~~an area that needs to be sealed, such as ~~the~~an appropriate area in ~~the~~a bearing unit, with ~~the~~ highest reliability.

## BRIEF DESCRIPTION OF DRAWINGS

[0036] Fig. 1 is a cross sectional view of ~~the~~an encoder-equipped sealing device in accordance with a first embodiment of the present invention, showing that two units of the encoder-equipped sealing device, for example, are placed ~~adjacently to~~adjacent each other in ~~the~~a horizontal direction so that they are oriented in one particular direction, although some non-critical parts are not shown;

[0037] Fig. 2 is a cross sectional view of the encoder-equipped sealing device in accordance with a second embodiment of the present invention, with some non-critical parts not being shown;

[0038] Fig. 3 is a cross sectional view of the encoder-equipped sealing device in accordance with a third embodiment of the present invention, with some non-critical parts not being shown;



[0039] Fig. 4 is a cross sectional view of the encoder-equipped sealing device in accordance with a fifth embodiment of the present invention, with some non-critical parts not being shown;

[0040] Fig. 5 is a cross sectional view of the encoder-equipped sealing device in accordance with a fourth embodiment of the present invention, with some non-critical parts not being shown;

[0041] Fig. 6 is a cross sectional view of the encoder-equipped sealing device in accordance with a sixth embodiment of the present invention, with some non-critical parts not being shown;

[0042] Fig. 7 is a side ~~elevation~~ elevational view of the encoder-equipped sealing device in accordance with a seventh embodiment of the present invention, with some parts being shown in cross section; and

[0043] Fig. 8 is a cross sectional view of ~~the~~ an encoder-equipped sealing device in accordance with the prior art, showing that two units of the encoder-equipped sealing device are placed ~~adjacently to~~ adjacent each other in ~~the~~ a horizontal direction so that they are oriented in one particular direction, although some non-critical parts are not shown;.

#### **DETAILED DESCRIPTION OF THE ~~INVENTION~~ PREFERRED EMBODIMENTS**

[0044] Several preferred embodiments of the present invention are now described below by referring to the accompanying drawings.

[0045] It should be noted that the encoder-equipped sealing device according to the prior art that has been described so far by referring to Fig. 8 and ~~the~~ an encoder-equipped sealing device according to ~~the~~ various embodiments of the present invention that will be described below by referring to Figs. 1 through 7 contain some common parts, elements or members. In the following description, ~~these~~ these common parts, elements or members are given same reference numerals, and are not described to avoid ~~the~~ duplication.

[0046] Referring first to Fig. 1, ~~the~~ an encoder-equipped sealing device according to a first embodiment of the present invention is described. In ~~the~~ encoder-equipped sealing devices 51 and 52, ~~the~~ seal element 3 includes a projecting portion 4a on ~~the~~ an end of ~~the~~ cylindrical portion 31a on ~~the~~ a side on which ~~the~~ flange portion 31b is located. The projecting portion 4a extends beyond ~~the~~ a side of the flange portion 31b opposite ~~the~~ a side on which ~~the~~ seal portion

6 is located and in ~~the~~a direction in which the cylindrical portion 31a extends. That is to say, the projecting portion 4a extends beyond the left side of the flange portion 31b in Fig. 1.

[0047] In the embodiment shown in Fig. 1, ~~the~~an end of the cylindrical portion 31a that is located on the left side and ~~the~~a base end of the flange portion 31b are formed in such a manner as to extend toward the left side. ~~The~~This before described portion extends toward the left side in Fig.1 and forms the projecting portion 4a.

[0048] Referring next to Fig. 2, ~~the~~an encoder-equipped sealing device according to a second embodiment of the present invention is described. This second embodiment is based on ~~the~~an inventive concept on which the first embodiment is based.

[0049] In the encoder-equipped sealing device shown in Fig 2, ~~the~~ seal element 3 includes an end 4b at ~~the~~an end of ~~the~~ cylindrical portion 31a on which ~~the~~ flange portion 31b is located. The end 4b forms a projecting portion as shown in Fig.2. The end 4b is formed by folding ~~the~~a base end of the flange portion 31b and the end of the cylindrical portion 31a, thereby overlapping each other in ~~the~~a direction in which the cylindrical portion 31a extends as shown in Fig.2.

[0050] Referring next to Fig. 3, ~~the~~an encoder-equipped sealing device according to a third embodiment of the present invention is described.

[0051] In the encoder-equipped sealing device shown in Fig 3, ~~the~~ seal element 3 includes a projecting portion 4c extending beyond ~~the~~a side of ~~the~~ flange portion 31b opposite ~~the~~a side on which ~~the~~ seal portion 6 is located and extending in ~~the~~a direction in which the cylindrical portion 31a extends. That is to say, the projecting portion 4c ~~extending~~extends beyond the left side of the flange portion 31b in Fig.3.

[0052] In the third embodiment shown in Fig. 3, the projecting portion 4c is formed by bending ~~the~~an end of the flange portion 31b toward the left side in Fig. 3. It should be noted that this embodiment may be varied such that the projecting portion 4c can be located on ~~the~~a middle portion of the flange portion 31b.

[0053] Referring next to Fig. 5, ~~the~~an encoder-equipped sealing device according to a fourth embodiment of the present invention is described.

[0054] In the encoder-equipped sealing device shown in Fig 5, ~~the~~ end portion 4d of ~~the~~ cylindrical portion 31a of the seal element 3 extending toward ~~the~~ other ~~another~~ seal element 2 extends in ~~the~~a direction in which the cylindrical portion 31a extends. And, the said-end portion

4d further extends beyond ~~the~~ a side of the other seal element 2 opposite the side on which the other seal element 2 faces opposite the seal element 3. That is to say, the end portion 4d of the cylindrical portion 31a of the seal element 3 extends beyond the right side of the seal element 2 in the direction in which the cylindrical portion 31a extends.

[0055] In the fourth embodiment shown in Fig. 5, an encoder 1 is arranged on ~~the~~ a side (right side in Fig. 5) of ~~the~~ flange portion 21b opposite ~~the~~ a side on which the flange portion 21b faces the seal element 3. ~~As~~ Since the end portion 4d of the cylindrical portion 31a of the seal element 3 extends beyond the side (right side in Fig. 5) of the seal element 2 opposite the side on which the seal element 2 faces the seal element 3, the end portion 4d extends beyond the right side of the encoder 1 in Fig. 5 and in the direction in which the cylindrical portion 31a extends.

[0056] Referring next to Fig. 6, ~~the~~ an encoder-equipped sealing device according to a sixth embodiment of the present invention is described.

[0057] In the encoder-equipped sealing device shown in Fig 6, ~~the~~ encoder 1 is arranged on ~~the~~ a side of ~~the~~ flange portion 21b of ~~the~~ seal element 2 opposite ~~the~~ a side on which the flange portion 21b faces opposite ~~the~~ seal element 3. That is to say, the encoder 1 is disposed on the right side of the flange portion 21b of the seal element 2. And, the flange portion 21b includes a projecting portion 4e that extends beyond ~~the~~ a surface of the encoder 1 and in ~~the~~ a direction in which ~~the~~ cylindrical portion 21a extends.

[0058] In the sixth embodiment shown in Fig. 6, the projecting portion 4e is formed by bending the end of the flange portion 21b, and the projecting portion 4e extends beyond the right side of the encoder 1 and in the direction in which the cylindrical portion 21a extends.

[0059] In any of the embodiments described above by referring to Figs. 1, 2, 3, 5 and 6, when two units of the encoder-equipped sealing device as designated by 51, 52 are placed one over the other adjacently to each other in a particular direction as shown in Fig. 1 so that ~~these~~ these units are oriented in one particular direction, ~~the~~ projecting portion 4a, ~~the~~ end portion 4b forming ~~the~~ projecting portion, the projecting portion 4c, the end 4d and the projecting portion 4e can exist between the two adjacent units 51 and 52.

[0060] ~~These~~ These projecting portions and ends that exist between the two adjacent units 51 and 52 can prevent the encoder 1 in one unit and the flange portion 31b in the other unit from contacting each other over ~~the~~ a wide area, as opposed to the case shown in Fig. 8.

[0061] Thus, ~~the~~a magnetic force produced from the encoder 1 in ~~the~~-unit 51 against the flange portion 31b in ~~the~~-unit 52 can be reduced greatly.

[0062] This can prevent ~~the~~-cohesion by ~~the~~-magnetic attraction from occurring between two adjacent units 51 and 52.

[0063] In particular, in each of the embodiments shown in Figs. 5 and 6, the end portion 4d or projecting portion 4e in one unit can abut ~~against~~-the flange portion 31b in the other adjacent unit, which can prevent the encoder 1 in ~~the~~-unit 51 from contacting the flange portion 31b in ~~the~~-unit 52. Thus, those embodiments are very advantageous in that ~~the~~-cohesion by ~~the~~ magnetic attraction between the two adjacent units 51 and 52 can be prevented.

[0064] It should be noted that in each of the embodiments shown in Figs. 1, 2 and 3, ~~the~~an area of contact between the encoder 1 in ~~the~~-unit 51 and the flange portion 31b in ~~the~~-unit 52 can be made as small as possible by modifying ~~the~~a size of the flange portions 21b, 31b as viewed vertically in ~~the~~-respective figures, ~~the~~a size of the encoder 1, ~~the~~a size of the projecting portion 4a, and ~~the~~a size of ~~the~~-end 4b forming ~~the~~a projecting portion, respectively.

[0065] In each of the embodiments shown in Figs. 5 and 6, ~~the~~-respective end portion 4d and projecting portion 4e may be extended further toward the right side in Figs. 5 and 6, respectively. In this way, ~~the~~a gap between the encoder 1 and ~~the~~-sensor 11, located adjacently to and opposite the encoder 1, can be covered like an umbrella by the end portion 4d and projecting portion 4e. Thus, the gap between the encoder 1 and sensor 11 can be protected from any foreign matter that might otherwise enter the gap.

[0066] In each of the embodiments described so far by referring to Figs. 1, 2, 3, 5 and 6, ~~the~~a gap between the units 51 and 52 that are located adjacently to each other ~~are~~is determined by ~~the~~-presence of the projecting portion 4a, the end portion 4b forming the projecting portion, the projecting portion 4c, the end portion 4d, and the projecting portion 4e. Thus, ~~these~~-~~these~~ projecting ~~portion~~ 4a, ~~etc.~~portions 4a-4e, which are made of metal, can ~~keep~~maintain the gap between the adjacent units 51 and 52 as-constant as it is originally designed.

[0067] Referring to Fig. 4, the encoder-equipped sealing device according to a fifth embodiment of the present invention is now described.

[0068] In the encoder-equipped sealing device shown in Fig ~~5~~4, ~~the~~-seal element 3 includes a recess 4f that is formed ~~on~~in ~~the~~-in a side of ~~the~~-flange portion 31b opposite ~~the~~a side on which ~~the~~-seal portion 6 is located. The ~~said~~-recess 4f extends toward ~~the~~a side on which the

seal portion 6 is located. That is to say, the recess 4f is formed at the left side of flange portion 31b in Fig. 4, ~~and~~ And the recess 4f extends toward the right side in Fig. 4.

[0069] When two units 51, 52 of the encoder-equipped sealing device are placed one over the other adjacently to each other so that they are oriented in one particular direction, as shown in Fig. 1, ~~the presence of the recess 4f can keep the~~ maintain an area of contact between the encoder 1 in one unit 51 and the flange portion 31b in the other unit 52 as small as possible. This can reduce ~~the a~~ magnetic force attracting two units 51 and 52, and can thus prevent the two units from attracting each other magnetically. This recess 4f may be formed by using ~~the a~~ knurling process, for example.

[0070] Referring next to Fig. 7, ~~the an~~ encoder-equipped sealing device according to a seventh embodiment of the present invention is described.

[0071] In the encoder-equipped sealing device shown in Fig 7, ~~the seal element 3 includes an elastic lateral side portion 5 formed on the a side of the flange portion 31b opposite the a side on which the seal portion 6 is located. The elastic lateral side portion 5 has undulations 4g formed thereon. This elastic lateral side portion 5 may be made of any elastic materials material, such as synthetic rubber, and synthetic resin and the like.~~

[0072] When two units 51, 52 of the encoder-equipped sealing device are placed one over the other adjacently to each other so that they are oriented in one particular direction, as shown in Fig. 1, the elastic lateral side portion 5 having the undulations 4g thereon can ~~keep the~~ maintain a gap between the two units 51 and 52 constant, thereby preventing ~~the cohesion by the~~ magnetic attraction that might occur between the two units 51 and 52.

[0073] In the embodiment shown in Fig. 7, it should be noted that the elastic lateral side portion 5 having the undulations 4g thereon exists between the encoder 1 in one unit 51 and the metal flange portion 31b in the other unit 52 that is located adjacently to ~~the unit 51~~. The elastic lateral side portion 5 can ~~keep~~ maintain the encoder 1 in the one unit 51 in soft contact with the metal flange portion 31b in the other unit 52, which will prevent the encoder 1 from being deformed or having ~~the high~~ molecular cohesion with the metal flange portion 31b.

[0074] In each of the embodiments shown in Figs. 1 through 7, it should be noted that the seal portion 6 includes radial lips 6a, 6b extending from ~~the a~~ side, at which cylindrical portion 31a exists, toward ~~the a~~ forward end of the flange portion 31b and in ~~the a~~ direction in which the cylindrical portion 31a extends, so ~~that extending as to extend~~ obliquely, and a side lip 6c

extending from ~~the~~a forward end of the flange portion 31b toward the cylindrical portion 31a and in ~~the~~a direction in which the cylindrical portion 31a extends, so ~~that~~extending as to extend obliquely.

[0075] It should also be noted that when ~~the~~ seal element 3 and seal element 2 are combined such that ~~the~~a space defined by the cylindrical portion 31a and flange portion 31b of the seal element 3, and ~~the~~a space defined by the cylindrical portion 21a and flange portion 21b of the seal element 2, can face opposite each other, the radial lips 6a, 6b can abut ~~the~~a circumferential surface of the cylindrical portion 21a, and the side lip 6c can abut ~~the~~an inner surface of the flange portion 21b.

[0076] The seal portion 6 may be made of any elastic ~~materials~~material such as synthetic rubber, synthetic resin and the like, as it is known to the art. It should be understood that the present invention is not limited to the embodiments of the seal portion 6 described above by referring to Figs. 1 through 7.

[0077] The encoder-equipped sealing device of the present invention ~~are~~is used by mounting it on ~~the~~a bearing unit of an automotive vehicle, which comprises an inner race and outer race ~~relatively~~rotating relative to each other, for example.

[0078] In each of the embodiments described so far by referring to Figs. 1 through 7, it is assumed that the seal element 2 in the encoder-equipped sealing device 51 is mounted on ~~the~~a rotational element on an automotive vehicle. For example, the encoder-equipped sealing device according to each of ~~these~~these embodiments has been described, assuming that the encoder-equipped sealing device is mounted on the bearing unit ~~with~~while mounting the seal element 2 in the encoder-equipped sealing device 51 on the rotational element, such as an inner race. It should be understood, however, the encoder-equipped sealing device according to each of the embodiments described and shown can be mounted on ~~the~~a bearing unit, comprising an inner race and outer race ~~relatively~~rotating relative to each other, ~~with~~while mounting the seal element 2 in the encoder-equipped sealing device 51 on the outer race, which is a rotational element, although this is not shown.

[0079] Although the present invention has been described with reference to several particular preferred embodiments thereof by referring to the accompanying drawings, it should be understood that the present invention is not limited to ~~these~~these embodiments, and various

changes and modifications may be made without departing from the spirit and scope of the invention as defined in the appended claims.

## ABSTRACT OF THE DISCLOSURE

An encoder-equipped sealing device, that is, ~~the~~a sealing device that has ~~the~~an encoder incorporated therein is disclosed, which comprises a combination of seal elements ~~(3, 2)~~, each of which includes an annular metal core ~~(31, 21)~~ having a substantially L-shaped cross section and including a cylindrical portion ~~(31a, 21a)~~ and a flange portion ~~(31b, 21b)~~ provided on one end of the cylindrical portion ~~(31a, 21a)~~ and extending in ~~the~~a direction perpendicular to ~~the~~a direction in which the cylindrical portion ~~(31a, 21a)~~ extends. One seal element, (3) of the two seal elements, ~~(3, 2)~~ and the other seal element (2) are combined such that ~~the~~a space defined by the cylindrical portion (31a) and flange portion (31b) of the one seal element, (3) and ~~the~~a space defined by the cylindrical portion (21a) and flange portion (21b) of the other seal element, (2) face opposite each other, wherein the one seal element (3) further includes an elastic seal portion (6) provided on the flange portion (31b) and arranged in the space defined by the cylindrical portion (31a) and flange portion ~~(31b)~~, and the other seal element (2) further includes a magnet-based encoder (1) provided on the flange portion ~~(21b)~~. The one seal element (3) further includes a projecting portion ~~(4a, 4b)~~ on ~~the~~an end of the cylindrical portion ~~(31a)~~ on ~~the~~a side on which the flange portion (31b) is located and extending beyond ~~the~~a side of the flange portion ~~(31b)~~ opposite ~~the~~a side on which the seal portion (6) is located and in ~~the~~a direction in which the cylindrical portion (31a) extends.